

Basic specification:

- ✓ Disk brakes
- ✓ Hopper with a capacity of 3,0 m³
- ✓ Safety grid in the hopper
- ✓ Auger from wear resistant steel
- ✓ Bag lifting device
- ✓ Winch for operating bag pan
- ✓ Wheels: 400/60R15
- ✓ Tunnel 2,7 m
- ✓ Hitch 40 mm on tractor drawbar
- ✓ Adjustable height drawbar

Optional:

- ✓ Tunnel 3,0 m
- ✓ Applicator with barrel holder and nozzles
- ✓ Hopper extension to 3,5 m
- ✓ Hitch ball K-80 on tractor drawbar

Specifications:

PTO speed	rpm	540
Tractor power	hp	100-160
Performance machine	ton/h	180-250

Dimensions of the machine:

Length	mm	5.210
Width	mm	3.405
Height	mm	2.705
Machine weight	kg	2.000



GS BAGGER D9

Low built, reliable, high capacity universal grain bagger for all sorts of grain with bagging capacity exceeding 250 ton/h



Jan-Dirk van der Tol
Tel. +31 514 571340
j.vandertol@eurobagging.com

www.eurobagging.com



Per Christerson Tel. +46-70-3216262 per@farmmac.com
Krister Wiengren Tel. +46-73-3335130 krister@farmmac.com

www.farmmac.com

Anders Wennerholm Tel. +46-70-6403438 anders@farmmac.com

DISCLAIMER: Grain Saver is continually being further developed. We reserve the right to change specifications, prices and models at any time. Illustrations and specifications are approximately binding.

www.grainsaver.com



www.grainsaver.com